

Blind rivet (Large flange)

Body	Aluminum(A5154)
Mandrel	Steel(Carbon steel)

NSA-LF			Domed head		
Adaptive Nosepiece (φmm)	Base hole (φmm)	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202-)
4.0	4.1 4.2	3.2~6.4	NSA54LFMP	30	096881
		4.8~8.0	NSA55LFMP	30	096775
		6.4~9.5	NSA56LFMP	25	096812
		9.5~12.7	NSA58LFMP	25	096850
4.8	4.9 5.0	1.6~3.2	NSA62LFMP	15	096898
		1.6~4.8	NSA63LFMP	15	096782
		3.2~6.4	NSA64LFMP	15	096829
		4.8~8.0	NSA65LFMP	12	096867
		6.4~9.5	NSA66LFMP	12	096904
		9.5~12.7	NSA68LFMP	12	096799
		12.7~15.9	NSA610LFMP	12	096836
		15.9~19.1	NSA612LFMP	8	096874
		19.1~22.3	NSA614LFMP	8	096911
		22.3~25.4	NSA616LFMP	8	096928

Blind rivet (Countersunk head)

Body	Aluminum(A5154)
Mandrel	Steel(Carbon steel)

NSA-K			Countersunk head		
Adaptive Nosepiece (φmm)	Base hole (φmm)	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202-)
2.4	2.5 2.6	1.6~3.2	NSA32KMP	75	096966
		3.2~6.4	NSA34KMP	75	097833
3.2	3.3 3.4	1.6~3.2	NSA42KMP	75	097048
		1.6~4.8	NSA43KMP	75	096935
		3.2~6.4	NSA44KMP	75	096973
		4.8~8.0	NSA45KMP	75	097017
		6.4~9.5	NSA46KMP	65	097055
		9.5~12.7	NSA48KMP	55	096942
4.0	4.1 4.2	1.6~3.2	NSA52KMP	65	096980
		1.6~4.8	NSA53KMP	55	097024
		3.2~6.4	NSA54KMP	55	097062
		4.8~8.0	NSA55KMP	50	096959
		6.4~9.5	NSA56KMP	45	096997
		9.5~12.7	NSA58KMP	45	097031
4.8	4.9 5.0	2.4~3.2	NSA62KMP	35	097079
		2.4~4.8	NSA63KMP	35	097086
		3.2~6.4	NSA64KMP	35	097123
		4.8~8.0	NSA65KMP	35	097161
		6.4~9.5	NSA66KMP	30	097208
		9.5~12.7	NSA68KMP	25	097093
		12.7~15.9	NSA610KMP	25	097130

AP rivet (Wide range)

Body	Aluminum(A5052)
Mandrel	Steel(Carbon steel)

AP			Domed head		
Adaptive Nosepiece (φmm)	Base hole (φmm)	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202-)
3.2	3.4 3.5	1.0~4.8	AP43MP	70	097482
		4.8~8.0	AP45MP	70	097529
4.0	4.2 4.3	1.2~6.4	AP54MP	60	097413
		1.6~6.4	AP64MP	35	097451
4.8	5.0 5.1	6.4~12.7	AP68MP	25	097499

Blind rivet (Colored)

Body	Aluminum(A5154)
Mandrel	Steel(Carbon steel)

CNSA			Domed head		
Color	Adaptive Nosepiece (φmm)	Base hole (φmm)	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton JAN Code (4963202-)
Bronze	3.2	3.3	1.0~3.2	CNSA42BRMP	65 097642
		3.4	1.6~4.8	CNSA43BRMP	65 097680
		3.4	3.2~6.4	CNSA44BRMP	60 097574
	4.0	4.1	1.2~3.2	CNSA52BRMP	55 097611
		4.2	1.6~4.8	CNSA53BRMP	50 097659
		4.2	3.2~6.4	CNSA54BRMP	50 097697
White	3.2	3.3	1.0~3.2	CNSA42WMP	65 097581
		3.4	1.6~4.8	CNSA43WMP	65 097628
		3.4	3.2~6.4	CNSA44WMP	60 097666
	4.0	4.1	1.2~3.2	CNSA52WMP	55 097703
		4.2	1.6~4.8	CNSA53WMP	50 097598
		4.2	3.2~6.4	CNSA54WMP	50 097635
Black	3.2	3.3	1.0~3.2	CNSA42BMP	65 097673
		3.4	1.6~4.8	CNSA43BMP	65 097710
		3.4	3.2~6.4	CNSA44BMP	60 097727
	4.0	4.1	1.2~3.2	CNSA52BMP	55 097758
		4.2	1.6~4.8	CNSA53BMP	50 097772
		4.2	3.2~6.4	CNSA54BMP	50 097796

Blind rivet (Shield type)

Body	Aluminum(A5056)
Mandrel	Steel(Carbon steel)

NSA-C			Domed head(Shield type)		
Adaptive Nosepiece (φmm)	Base hole (φmm)	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202-)
4.0	4.1 4.2	1.2~3.2	NSA52CMP	35	097536
		1.6~4.8	NSA53CMP	30	097420
		3.2~6.4	NSA54CMP	30	097468
	4.8	4.8~8.0	NSA55CMP	25	097505
		6.4~9.5	NSA56CMP	25	097543
		9.5~12.7	NSA58CMP	15	097604
4.8	4.9 5.0	1.6~3.2	NSA62CMP	30	097437
		1.6~4.8	NSA63CMP	30	097475
		3.2~6.4	NSA64CMP	30	097512
	5.0	4.8~8.0	NSA65CMP	25	097550
		6.4~9.5	NSA66CMP	25	097567
		9.5~12.7	NSA68CMP	15	097604

S-bolt (High strength)

Body	Steel(Carbon steel)
Mandrel	Steel(Carbon steel)

SNS			Domed head / Countersunk head		
Type	Adaptive Nosepiece (φmm)	Base hole (φmm)	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton JAN Code (4963202-)
Domed head	4.8	4.9 5.0	1.7~6.9	SNS48069MP	18 097734
		5.0	1.7~11.0	SNS48110MP	18 097765
Countersunk head	6.4	6.6 7.0	2.1~9.5	SNS64095MP	15 097789
		7.0	2.1~15.9	SNS64159MP	10 097802
			3.2~12.0	SNS64120KP	15 097741



BLIND RIVETS
ECOPAC

Blind rivet ECO package



Launch
of new
package

MADE IN
JAPAN

ECOLOGY

Packed in reusable resin case

Empty case is reusable for other purposes (parts case, accessory case, etc.)

ECONOMY

Affordable
small-quantity package

You can purchase as many necessary items as required.

KEEP

● Packed in durable resin case, suitable for storage

SELECT

- Wider lineup of materials and sizes
- Material identification by label color
- Easy to purchase because of material-based pricing

Monodzukuri solutions for professionals.
Monodzukuri fun for everyone.

LOBTEX CO.,LTD.

Call center TEL(072)980-1111 FAX(072)980-1166

Homepage <http://www.lobtex.co.jp/>



BLIND RIVETS (Domed head)

BLIND RIVETS ECOPAC

Body Aluminum(A5154)
Mandrel Steel(Carbon steel)



BLIND RIVETS ECOPAC

Body Aluminum(A5052)
Mandrel Aluminum(A2017)



BLIND RIVETS ECOPAC

Body Stainless steel(SUS305)
Mandrel Stainless steel (corresponds to SUS304)



BLIND RIVETS ECOPAC

Body Stainless steel(SUS305)
Mandrel Steel(Carbon steel)



BLIND RIVETS ECOPAC

Body Steel(Carbon steel)
Mandrel Steel(Carbon steel)




NSA		Domed head			
Adaptive Nosepiece	Base hole	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202)
2.4	2.5 ∩ 2.6	1.0~3.2	NSA32MP	80	095808
		1.6~4.8	NSA33MP	80	095846
		3.2~6.4	NSA34MP	80	095884
3.2	3.3 ∩ 3.4	1.0~1.6	NSA41MP	80	095921
		1.0~3.2	NSA42MP	80	095815
		1.6~4.8	NSA43MP	80	095853
		3.2~6.4	NSA44MP	80	095891
		4.8~8.0	NSA45MP	75	095938
		6.4~9.5	NSA46MP	65	095822
		9.5~12.7	NSA48MP	55	095860
		12.7~15.9	NSA410MP	30	095907
4.0	4.1 ∩ 4.2	1.2~3.2	NSA52MP	65	095839
		1.6~4.8	NSA53MP	60	095877
		3.2~6.4	NSA54MP	60	095914
		4.8~8.0	NSA55MP	50	095952
		6.4~9.5	NSA56MP	45	095969
		9.5~12.7	NSA58MP	45	097819
		12.7~15.9	NSA510MP	25	096041
		15.9~19.1	NSA512MP	25	096089
4.8	4.9 ∩ 5.0	1.6~3.2	NSA62MP	35	095976
		1.6~4.8	NSA63MP	35	096010
		3.2~6.4	NSA64MP	35	096058
		4.8~8.0	NSA65MP	35	096096
		6.4~9.5	NSA66MP	30	095983
		9.5~12.7	NSA68MP	25	096027
		12.7~15.9	NSA610MP	25	096065
		15.9~19.1	NSA612MP	20	096102
		19.1~22.3	NSA614MP	12	095990
		22.3~25.4	NSA616MP	12	096034

NA		Domed head			
Adaptive Nosepiece	Base hole	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202)
2.4	2.5 ∩ 2.6	1.0~3.2	NA32MP	50	097178
		1.6~4.8	NA33MP	50	097215
		3.2~6.4	NA34MP	50	097109
3.2	3.3 ∩ 3.4	1.0~1.6	NA41MP	50	097147
		1.0~3.2	NA42MP	50	097185
		1.6~4.8	NA43MP	45	097222
		3.2~6.4	NA44MP	45	097116
		4.8~8.0	NA45MP	45	097154
		6.4~9.5	NA46MP	40	097192
		9.5~12.7	NA48MP	35	097239
		12.7~15.9	NA410MP	20	097246
4.0	4.1 ∩ 4.2	1.2~3.2	NA52MP	35	097321
		1.6~4.8	NA53MP	30	097369
		3.2~6.4	NA54MP	30	097253
		4.8~8.0	NA55MP	30	097291
		6.4~9.5	NA56MP	30	097338
		9.5~12.7	NA58MP	25	097376
		12.7~15.9	NA510MP	15	097260
		15.9~19.1	NA512MP	15	097307
4.8	4.9 ∩ 5.0	1.6~3.2	NA62MP	20	097345
		1.6~4.8	NA63MP	20	097383
		3.2~6.4	NA64MP	20	097277
		4.8~8.0	NA65MP	20	097314
		6.4~9.5	NA66MP	20	097352
		9.5~12.7	NA68MP	20	097390
		12.7~15.9	NA610MP	15	097406
		15.9~19.1	NA612MP	15	097444

NST		Domed head			
Adaptive Nosepiece	Base hole	appropriate caulking plate thickness MIN~MAX (mm)	Model No.	Q'ty/ carton	JAN Code (4963202)
2.4	2.5 ∩ 2.6	1.0~3.2	NST32MP	50	096478
		3.2~6.4	NST34MP	50	096515
3.2	3.3 ∩ 3.4	1.0~1.6	NST41MP	45	096553
		1.0~3.2	NST42MP	45	096591
		1.6~4.8	NST43MP	40	096607
		3.2~6.4	NST44MP	40	096645
		4.8~8.0	NST45MP	35	096683
		6.4~9.5	NST46MP	30	096720
		9.5~12.7	NST48MP	30	096614
4.0	4.1 ∩ 4.2	1.2~3.2	NST52MP	30	096652
		1.6~4.8	NST53MP	30	096690
		3.2~6.4	NST54MP	25	096737
		4.8~8.0	NST55MP	25	096621
		6.4~9.5	NST56MP	25	097826
		9.5~12.7	NST58MP	20	096706
4.8	4.9 ∩ 5.0	1.6~3.2	NST62MP	20	096744
		1.6~4.8	NST63MP	15	096638
		3.2~6.4	NST64MP	15	096676
		4.8~8.0	NST65MP	15	096713
		6.4~9.5	NST66MP	15	096751
		9.5~12.7	NST68MP	12	096768
		12.7~15.9	NST610MP	12	096805
		15.9~19.1	NST612MP	12	096843

● size
W65mm × H22mm × D92mm



Safety instructions

- To work with the "S-bolt" blind rivet, ensure conformity to our specified dimensions of appropriate caulking plate thickness and prepared hole diameters, and give thorough consideration to safety factors.
- Please read the explanation indicated on a package before use well.
- Specifications may be changed for improvement of the product without prior notices.
- Listed prices do not include VAT. Please ask our distributor in case of purchases.
- Since dimensions, weights, etc. are nominal, there possibly are changes of some numerical values.

材質

Model	Body	Mandrel	Label color
NSA	Aluminum	Steel	
NA	Aluminum	Aluminum	
NST	Stainless steel	Stainless steel	
NSS	Stainless steel	Steel	
NS	Steel	Steel	

Type

Blind rivet (Domed head) NSA/NA/NST/NSS/NS

Blind rivet of the standard shape. Combinations of five types of materials are available in our product lineup, which can be selected according to the type of workpiece. Abundant size variations can meet various needs.



Blind rivet (Large flange) NSA-LF

Thank to a large flange diameter, the rivet is suitable for various soft workpieces, such as plastic, FRP and wood.



AP rivet (Wide range) AP

Because the rivet covers a wide range of caulking plate thickness, one size can handle diverse applications. With excellent air tightness, the rivet is suitable for soft workpieces.



Blind rivet (Shield type) NSA-C

With the shield head, the rivet provides excellent water-proofing, without popping its head off.



Blind rivet (Countersunk head) NSA-K

Since the flange is countersunk, the mounting surface can be flattened.



Blind rivet (Colored) CNSA-BR/CNSA-W/CNSA-B

The flange is coated, enabling beautiful finishing.



S-bolt (High strength) SNS/SNS-K

With the original lock mechanism, tightening condition can be visually checked. The swelled shank enables the rivet to fill the prepared hole, providing high strength and seismic resistance.

